

Quad Operational Amplifier

RoHS

Rev.1. Jan. 2010.



VSP MIKRON

LM324M

DESCRIPTION


The LM324 consists of four independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltages. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage.

Application areas include transducer amplifiers, DC gain blocks and all the conventional op amp circuits.

FEATURES

- Wide range of supply voltages
- Low supply current drain independent of supply voltage
- Low input biasing current
- Low input offset voltage and offset current
- Input common-mode voltage range includes ground
- Differential input voltage range equal to the power supply voltage
- DC voltage gain 100 V/mV Typ
- Internally frequency compensation

PACKAGE INFORMATION



ELECTRICAL CHARACTERISTICS

at specified free-air temperature, $V_{CC} = 5V$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS*	LM324			UNIT
		MIN	TYP	MAX	
V_{IO} Input offset voltage	$V_{CC} = 5V$ to MAX, $V_{IC} = V_{ICB}$ min, $V_o = 1.4V$	25 °C Full range		3 7 9	mV
αV_{IO} Average temperature coefficient of input offset voltage		Full range		7	µV/°C
I_{IO} Input offset current	$V_o = 1.4V$	25 °C Full range	2 50 150	nA	
αI_{IO} Average temperature coefficient of input offset current		Full range		10	pA/°C
I_B Input bias current	$V_o = 1.4V$	25 °C Full range	-20 -250 -500	nA	
V_{ICB} Common-mode input voltage range	$V_{CC} = 5V$ to MAX	25 °C Full range	0 to $V_{CC} - 1.5$ 0 to $V_{CC} - 2$		V
V_{OH} High-level output voltage	$R_L = 2 k\Omega$	25 °C	$V_{CC} - 1.5$		V
	$V_{CC} = \text{MAX}$, $R_L = 2k\Omega$	Full range	26		
	$V_{CC} = \text{MAX}$, $R_L = 10 k\Omega$	Full range	27 28		
V_{OL} Low-level output voltage	$R_L = 10 k\Omega$	Full range		5 20	mV
A_{VD} Large-signal differential voltage amplification	$V_{CC} = 15 V$, $V_o = 1V$ to $11 V$, $R_L \geq 2 k\Omega$	25 °C Full range	25 100 15		V/mV
CMRR Common-mode rejection ratio	$V_{CC} = 5V$ to MAX, $V_{IC} = V_{ICB}$ min	25 °C	65	80	dB
k_{SVR} Supply voltage rejection ratio ($\Delta V_{CC}/\Delta V_{IO}$)	$V_{CC} = 5V$ to MAX	25 °C	65	100	dB
Vo1/Vo2 Crosstalk attenuation	f=1kHz to 20 kHz	25 °C		120	dB
I_O Output current	$V_{CC} = 15 V$, $V_{ID} = 1V$, $V_o = 0$	25 °C Full range	-20 -30 -10		mA
	$V_{CC} = 15 V$, $V_{ID} = -1V$, $V_o = 15V$	25 °C Full range	10 20 5		
	$V_{ID} = -1V$, $V_o = 200 mV$	25 °C	12	30	µA
I_{OS} Short-circuit output current	V_{CC} at 5 V, GND at -5V, $V_o = 0$	25 °C		±40 ±60	mA
I_{CC} Supply current (four amplifiers)	$V_o = 2.5 V$, No load	Full range		1.5 2.4	mA
	$V_{CC} = \text{MAX}$, $V_o = 0.5V_{CC}$, No load	Full range		1.1 3	

* All characteristics are measured under open loop conditions with zero common-mode input voltage unless otherwise specified. "MAX" V_{CC} for testing purposes is 30 V. Full range is 0 °C to 70 °C


Quad Operational Amplifier



VSP MIKRON

LM324M

PAD LOCATION LM324M



Chip Size: 1.09 x 1.12 mm²

Wafer Thickness: $460 \pm 30 \mu\text{m}$ (or $350 \pm 30 \mu\text{m}$, $280 \pm 30 \mu\text{m}$)

Top metal: AlSi

Backside metal: - (or Ti-Ni (V)-Ag)

Wafer size: 100 mm

PAD LOCATION COORDINATES

Pad N	Pad Name	Pad size ($\mu\text{m} \times \mu\text{m}$)	Coordinates, μm		Pad N	Pad size ($\mu\text{m} \times \mu\text{m}$)	Pad Name	Coordinates, μm	
			X	Y				X	Y
1	#1 OUT	90 x 90	112	477	8	90 x 90	#3 OUT	977	642
2	#1 IN-	90 x 90	112	112	9	90 x 90	#3 IN-	977	1007
3	#1 IN+	90 x 90	390	112	10	90 x 90	#3 IN+	700	1007
4	V _{CC}	90 x 90	545.0	112	11	90 x 90	GND	545	1007
5	#2 IN+	90 x 90	700	112	12	90 x 90	#4 IN+	390	1007
6	#2 IN-	90 x 90	977	112	13	90 x 90	#4 IN-	112	1007
7	#2 OUT	90 x 90	977	477	14	90 x 90	#4 OUT	112	642